

PRODUCT SPECIFICATIONS

TrapBag

PROPERTY	UNIT	TBR60	TBRD60	TBR120
Fabric Specifications				
Grab Tensile Strength	MD x CMD	1.7kN x 1.25kN	1.5kN x 1.4kN	1.7kN x 1.25kN
Wide Width	MD x CMD	30kN/m x 30kN/m	30kN/m x 30kN/m	30kN/m x 30kN/m
Wide Width Elongation	MD x CMD	12% x 14%	11% x 10%	12% x 14%
Trap Tear	MD x CMD	500N x 475N	450N x 300N	500N x 475N
CBR Puncture	N	3,750N	4,350N	3,750N
UV Resistance	%	70%	80%	70%
Color		Green	Black	Green
Yarn Type		Tape	Monofilament	Tape
Treatment		Coated	Coated	Coated
Number of Plies in Bag		1	2	1
Packaging				
Height	Each cell	0.6m (2ft)	0.6m (2ft)	1.22m (4ft)
Width	Each cell	0.75m (2.5ft)	0.75m (2.5ft)	1.0m (3.3ft)
Depth	Each cell	0.9m (3ft)	0.9m (3ft)	1.45m (4.8ft)
Volume	Each cell	0.375m ³ (0.5yd ³)	0.375m ³ (0.5yd ³)	1.65m ³ (2.2yd ³)
Total Cells	Per set	20	20	15

Disclaimer: The information provided by Nilex is believed to be correct and is generally based on information supplied by the manufacturers of the product offered. Any recommendations made by Nilex concerning uses or applications of our products are also believed to be reliable; however, Nilex has no control over design execution, and field conditions of the project which incorporate the product. Nilex disclaims all warranties, expressed or implied, including, without limitation, the warranties of merchantability and/or fitness for a particular purpose.